

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

BI

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>C07C 17/20, 19/08, 17/278, 19/01</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 96/01797</b> <b>(43) International Publication Date:</b> 25 January 1996 (25.01.96)
<b>(21) International Application Number:</b> PCT/US95/08404 <b>(22) International Filing Date:</b> 5 July 1995 (05.07.95)  <b>(30) Priority Data:</b> 08/273,553 11 July 1994 (11.07.94) US  <b>(71) Applicant:</b> ALLIEDSIGNAL INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). <b>(72) Inventors:</b> VANDERPUY, Michael; 32 Joanne Lane, Cheektowaga, NY 14227 (US). THENAPPAN, Alagappan; 30 Butternut Road, Cheektowaga, NY 14227 (US). <b>(74) Agent:</b> CRISS, Roger, H.; AlliedSignal Inc., Law Dept. (C.A. McNally), 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).		<b>(81) Designated States:</b> AU, BR, CA, CN, CZ, HU, JP, KR, MX, UA, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> PROCESS FOR THE MANUFACTURE OF 1,1,1,3,3-PENTAFLUOROPROPANE  <b>(57) Abstract</b>  This invention is related to the preparation of hydrofluorocarbons (HFCs). Specifically, it relates to the fluorination of a compound of the formula: $CF_yCl_{3-y}CH_2CHF_wCl_{2-w}$ wherein $w = 0$ or $1$ , and $y = 0 - 3$ , with hydrogen fluoride in the presence of a fluorination catalyst under conditions sufficient to produce a compound of the formula: $CF_3CH_2CF_2H$ , $CF_3CH_2CF_2H$ or HFC 245fa may be used as a blowing agent, a propellant, and a heat transfer agent.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				


**PROCESS FOR THE MANUFACTURE OF  
1,1,1,3,3-PENTAFLUOROPROPANE**

**BACKGROUND OF THE INVENTION**

5

This invention relates to a novel method of manufacturing 1,1,1,3,3-pentafluoropropane,  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ , which is referred to in the art as HFC-245fa. Specifically, the invention relates to the fluorination with hydrogen fluoride of a compound of the formula:

10



wherein  $w = 0$  or  $1$ , and  $y = 0 - 3$ , in the presence of a fluorination catalyst to produce HFC-245fa.

15

HFC-245fa has physical properties, including a boiling point of about  $14^\circ\text{C}$ , which make it particularly attractive as a blowing agent. (See Ger. Offen, DE 3,903,336, 1990 (EP 381,986 A)). It also has the ability to function as an aerosol propellant (U.S. Patent 2,942,036 to Smith and Woolf) in a manner similar to trichlorofluoromethane, which is referred to in the art as CFC-11, and as a heat transfer agent. (Jpn. Kokai Tokyo Koho JP 02,272,086 in 114 Chemical Abstracts 125031q (1991)).

20

Traditionally, chlorofluorocarbons (CFCs) like CFC-11 and dichlorodifluoromethane (CFC-12) have been used as refrigerants, blowing agents and propellants. These materials, however, are believed to contribute to stratospheric ozone depletion. The fluorocarbon industry therefore has focused its attention on developing stratospherically safer alternatives to these materials. HFC-245fa is a candidate replacement material since it functions in substantially the same way as the CFCs but is zero ozone depleting. Because the demand for these and other low or zero ozone depleting materials will increase dramatically in the future, commercially viable processes for their preparation are needed.

30

Only two methods for manufacturing HFC-245fa (which are not hydrofluorination reactions) are reported in the art. However, these methods are not without their shortcomings. Knunyants, et al., *Catalytic Hydrogenation of Perfluoro Olefins*, 55 Chemical Abstracts 349f (1961), discloses the reduction of 1,1,1,3,3-pentafluoropropene to HFC-245fa. Because this process includes multiple steps, it is inefficient and uneconomical. Burdon, et al., *Partial Fluorination of Tetrahydrofuran with Cobalt Trifluoride*, J. Chem. Soc. (C), 1739 (1969), discloses the elemental

35

fluorination of tetrahydrofuran to produce HFC-245fa. This process suffers the disadvantage that it produces a host of other by-products, thus reducing the yield of the desired product.

- 5 As far as hydrofluorination reactions are concerned, there are no such methods for the production of HFC-245fa reported in the art, let alone fluorination reactions which use 1,1,1,3,3-pentachloropropane ( $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ ) as the starting material to produce HFC-245fa. Although the conversion of  $-\text{CCl}_3$  groups to  $-\text{CF}_3$  groups is well-known in the art, attempts to fluorinate terminal  $-\text{CHCl}_2$  or  $-\text{CHClF}$  groups to -
- 10  $\text{CHF}_2$  groups in compounds having more than two carbons, (in particular compounds of the formula  $\text{RCH}_2\text{CHCl}_2$  and  $\text{RCH}_2\text{CHFX}$  wherein X is Cl or Br and R is an alkyl group having at least one carbon atom), have not been successful. See Henne, et al., *Fluoroethanes and Fluoroethylenes*, 58 J. Am. Chem. Soc. 889 (1936).
- 15 Tarrant, et al., *Free Radical Additions Involving Fluorine Compounds. IV. The Addition of Dibromodifluoromethane to Some Fluoroolefins*, 77 J. Am. Chem. Soc. 2783 (1955) report the fluorination of compounds of the type  $\text{CF}_2\text{BrCH}_2\text{CHFBr}$  with hydrogen fluoride (HF) in the presence of a Sb(V) salt catalyst, such as  $\text{SbCl}_5$  and  $\text{TaF}_5$ . However, this method produced only a 14% yield of  $\text{CF}_3\text{CH}_2\text{CHFBr}$  at
- 20  $125^\circ\text{C}$ , and only a modest improvement in yield at  $170^\circ\text{C}$ . Even at elevated temperatures, no HFC-245fa was produced.

### DESCRIPTION OF THE INVENTION


- 25 We have discovered that the drawbacks associated with the prior art processes for manufacturing 1,1,1,3,3-pentafluoropropane or HFC-245fa can be eliminated by the process of our invention. That is, we have discovered an efficient and economical means of manufacturing HFC-245fa on a commercial scale, which uses readily available raw materials and which produces HFC-245fa in high yield.

30

The invention relates to a process for manufacturing 1,1,1,3,3-pentafluoropropane comprising:

- 1) reacting a compound of the formula:

35



wherein  $w = 0$  or  $1$ , and  $y = 0 - 3$ , with hydrogen fluoride in the presence of a fluorination catalyst under conditions sufficient to produce a compound of the formula  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ ; and

2) optionally recovering a compound of the formula  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ .

The organic starting materials corresponding to the formula  $\text{CF}_y\text{Cl}_{3-y}\text{CH}_2\text{CHF}_w\text{Cl}_{2-w}$ , wherein  $w = 0$  or  $1$ , and  $y = 0 - 3$ , include  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ ,  $\text{CF}_3\text{CH}_2\text{CHCl}_2$ ,  $\text{CFCl}_2\text{CH}_2\text{CHCl}_2$ ,  $\text{CF}_2\text{ClCH}_2\text{CHCl}_2$ ,  $\text{CFCl}_2\text{CH}_2\text{CHFCl}$ ,  $\text{CF}_2\text{ClCH}_2\text{CHFCl}$ , and  $\text{CF}_3\text{CH}_2\text{CHFCl}$ . The preferred starting material is  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ .

These materials are not commercially available. However, they may be prepared by any means well-known in the art. See, for example, B. Boutevin, et al., *Monofunctional Vinyl Chloride Telomers. I. Synthesis and Characterization of Vinyl Chloride Telomer Standards*, 18 Eur. Polym. J. 675 (1982) in 97 Chemical Abstracts 182966c (1982); and Kitora, et al., *Selective Additions of Polyhalogenated Compounds to Chloro Substituted Ethenes Catalyzed by a Copper Complex*, 44(2) React. Kinet. Catal. Lett. 415 (1991). See also the method disclosed in Examples 1 and 2 below. When  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  is the starting material, it is preferably prepared according to the method provided in Example 1 below. Alternatively,  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  may be prepared by the reduction of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  (see Example 2) as well as by photochlorination of  $\text{CCl}_3\text{CH}_2\text{CH}_2\text{Cl}$ .

Any water in the HF will react with and deactivate the fluorination catalyst. Therefore, substantially anhydrous HF is preferred. By "substantially anhydrous" we mean that the HF contains less than about 0.05 weight % water and preferably contains less than about 0.02 weight % water. However, one of ordinary skill in the art will appreciate that the presence of water in the catalyst can be compensated for by increasing the amount of catalyst used. HF suitable for use in the reaction may be purchased from AlliedSignal Inc. of Morristown, New Jersey.

Based on reaction stoichiometry, the required mole ratio of HF to organics (i.e.,  $\text{CF}_y\text{Cl}_{3-y}\text{CH}_2\text{F}_w\text{Cl}_{2-w}$ ) is  $5-y-w$  (or the number of chlorine atoms in the organic starting material) to 1.0. HF is preferably used in an amount from about 1 to about 15 times the stoichiometric amount of HF to organics, and more preferably from about 6 to about 15 times the stoichiometric amount of HF to organics.

Fluorination catalysts useful in the process of the invention include: (I.) pentavalent antimony, niobium, arsenic and tantalum halides; (II.) pentavalent antimony, niobium, arsenic and tantalum mixed halides; and (III.) mixtures of

pentavalent antimony, niobium, arsenic and tantalum halide catalysts. Examples of catalysts of group (I.) include antimony pentachloride and antimony pentafluoride. Examples of catalysts of group (II.) include  $\text{SbCl}_2\text{F}_3$  and  $\text{SbBr}_2\text{F}_3$ . Examples of catalysts of group (III.) include a mixture of antimony pentachloride and antimony pentafluoride.

Pentavalent antimony, niobium, arsenic and tantalum halides are commercially available, and mixed halides thereof are created *in situ* upon reaction with HF. Antimony pentachloride is preferred because of its low cost and availability.

10 Pentavalent antimony mixed halides of the formula  $\text{SbCl}_n\text{F}_{5-n}$  where n is 0 to 5 are more preferred. The fluorination catalysts used in this invention preferably have a purity of at least about 97%. Although the amount of fluorination catalyst used may vary widely, we recommend using from about 5 to about 50%, or preferably from about 10 to about 25% by weight catalyst relative to the organics.

15 It may be advantageous to periodically regenerate the catalyst due to the dissociation of the pentavalent catalyst over time. This may be accomplished by any means well known in the art. The catalyst may be regenerated, for example, by adding chlorine (in an amount of from about 1 to about 10 mole percent relative to the amount of pentavalent catalyst initially present in the reactor) to the combination

20 stream comprised of organics of the formula  $\text{CF}_y\text{Cl}_{3-y}\text{CH}_2\text{CHF}_w\text{Cl}_{2-w}$ , and the recycled stream comprised of under-fluorinated materials and HF. The chlorine, which is continuously added to the process of this invention when operating in a continuous mode (and periodically added when operating in a batch mode), oxidizes the catalyst

25 from the trivalent to the pentavalent state. One of ordinary skill in the art can readily determine without undue experimentation the amount of chlorine to be added in order to optimize the use of the catalyst.

The temperature at which the fluorination reaction is conducted and the period of reaction will depend on the starting material and catalyst used. One of ordinary skill in the art can readily optimize the conditions of the reaction without undue experimentation to get the claimed results, but the temperature will generally be in the range of from about 50 to about 175 °C, and preferably from about 115 to about 155 °C, for a period of, for example, from about 1 to about 25 hours, and preferably from

30 about 2 to about 8 hours.

Pressure is not critical. Convenient operating pressures range from about 1500 to about 5000 KPa, and preferably from about 1500 to about 2500 KPa.

## 5

The equipment in which the fluorination reaction is conducted is preferably made of corrosion resistant material such as Inconel or Monel.

5 HFC-245fa may be recovered from the mixture of unreacted starting materials, by-products, and catalyst by any means known in the art, such as distillation and extraction. As illustrated in Example 3, at the end of the heating period, i.e. the amount of time for complete reaction in batch mode operations, the fluorination reaction product and remaining HF may be vented through a valve on the autoclave  
10 head, which in turn is connected to an acid scrubber and cold traps to collect the product. Alternatively, unreacted HF and organics may be vented and condensed, and the HF layer recycled to the reactor. The organic layer can then be treated, i.e. washed with an aqueous base, to remove dissolved HF and distilled. This isolation procedure is particularly useful for a continuous fluorination process. Under-fluorinated  
15 materials, such as  $\text{CF}_3\text{CH}_2\text{CHCl}$ , may be recycled in subsequent runs.

In another embodiment, the invention relates to a process for the manufacture of 1,1,1,3,3-pentafluoropropane which comprises:

- 20 1. reacting  $\text{CCl}_4$  and vinyl chloride in the presence of a telomerization catalyst under conditions sufficient to produce a compound of the formula  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ ;
- 25 2. reacting a compound of the formula  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  with hydrogen fluoride in the presence of a fluorination catalyst under conditions sufficient to produce a compound of the formula  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ ; and
3. optionally recovering a compound of the formula  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ .

30 The telomerization of vinyl chloride by reaction with carbon tetrachloride to produce  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  is known in the art. See, for example, B. Boutevin, et al., *Monofunctional Vinyl Chloride Telomers. I. Synthesis and Characterization of Vinyl Chloride Telomer Standards*, 18 Eur. Polym. J. 675 (1982) in 97 Chemical Abstracts 182966c (1982); and Kotora, et al., *Selective Additions of Polyhalogenated*  
35 *Compounds to Chloro Substituted Ethenes Catalyzed by a Copper Complex*, 44(2) React. Kinet. Catal. Lett. 415 (1991).

The starting materials for the telomerization reaction, i.e. carbon tetrachloride and vinyl chloride, are available from commercial sources. The molar ratio of  $\text{CCl}_4$  to vinyl chloride is about 0.5:10, preferably about 1:8 (in order to minimize the formation of higher telomers), and most preferably about 1:5.

5

The telomerization of vinyl chloride can be initiated by any commercially available catalyst known in the art to be useful in initiating and catalyzing the telomerization of carbon tetrachloride and vinyl chloride. Suitable catalysts include, but are not limited to, organic peroxides, metallic salts, and metal carbonyls. Copper and iron salt catalysts, such as cuprous chloride ( $\text{CuCl}$ ), cuprous iodide ( $\text{CuI}$ ), and iron chloride ( $\text{FeCl}_2$ ), are preferred. The amount of catalyst used in the telomerization reaction is at least about 0.1 to about 50 mmol, and preferably about 1 to about 20 mmol per mole of organics (i.e.,  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ ).

15 An amine co-catalyst, such as an alkanol amine, alkyl amine, and aromatic amine, may optionally be used in order to allow for the use of milder conditions in the telomerization process. Examples of suitable amine co-catalysts include ethanol amine, butyl amine, propyl amine, benzylamine, and pyridine. 2-propylamine is the most preferred co-catalyst. Such co-catalysts are commercially available. When a co-catalyst is used, it should be used in an amount from about 1 to about 10 moles per mole of catalyst, i.e., e.g. copper salt.

25 In order to dissolve the catalyst, a solvent, which is inert to the reactants and the desired product, may be used in the telomerization reaction. Suitable solvents include, but are not limited to, commercially available acetonitrile, dimethylsulfoxide, dimethylformamide, tetrahydrofuran, isopropanol, and tertiary butanol. Acetonitrile is preferred because of ease of handling and stability. The amount of solvent used ranges from about 5 times the amount of catalyst used on a mole basis to about 80 percent of the total volume of the total telomerization reaction mixture (i.e., solvent, catalyst, co-catalyst, carbon tetrachloride, vinyl chloride), and more preferably between about 10 to 50 times the amount of catalyst used on a mole basis.

35 The temperature at which the telomerization reaction is conducted and the period of reaction will depend on the catalyst selected, the presence of a co-catalyst, and the solubility of the catalyst system in the solvent. One of ordinary skill in the art can readily optimize the conditions of the reaction without undue experimentation to get the claimed results but the temperature will generally be in the range of from about 25 to about 225 °C, preferably from about 50 to about 150 °C. The period of reaction

will generally range from about 3 to about 72 hours, preferably from about 10 to about 24 hours.

Pressure is not critical.

5

Preferably the telomerization reaction is conducted in a conventional apparatus, such as an autoclave made of corrosion resistant materials such as Teflon and glass.

10 Preferably, the telomerization product is recovered from by-products, solvent, catalyst and co-catalyst prior to the fluorination reaction to substantially eliminate the production of by-products in the fluorination step. The telomerization product may be recovered by any means well known in the art such as distillation and extraction. Optionally, the telomerization product may be further purified by additional distillation.

15 Due to the toxicity of vinyl chloride, other procedures for preparing  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  may be employed. See Example 2 (reduction of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ ). Alternatively,  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  may be prepared according to the well-known telomerization reaction of vinylidene chloride with carbon tetrachloride.

20 **Example 1. Preparation of  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  from  $\text{CCl}_4$  and  $\text{CH}_2=\text{CHCl}$**

A 600-mL monel autoclave equipped with mechanical stirrer was charged with 1 g CuCl, 156.6 g  $\text{CCl}_4$  and 75 mL acetonitrile. The contents were cooled in an ice bath, and the autoclave was closed and evacuated briefly. 36.7 g of vinyl chloride was then added, and the contents stirred and heated to 135 °C for 16 hours. The volatile materials were removed by distillation at atmospheric pressure. Distillation at 23 mm Hg resulted in 90.0 g (71% yield based on vinyl chloride added) of a colorless liquid. The identity of this liquid was confirmed via proton nuclear magnetic resonance ("NMR") to be  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  (boiling point 72-74 °C.  $^1\text{H}$  NMR ( $\text{CDCl}_3$ ):  $\delta$  6.15 (t, 1 H), 3.7 (d, 2 H)).

30

**Example 2. Preparation of  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  by reduction of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$**

A 600-mL monel autoclave equipped with mechanical stirrer was charged with 199.9 g  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ , 199.5 g isopropanol, and 4 g CuI. The autoclave was closed and evacuated briefly. The contents were heated to 120 - 125 °C for 16 hours. The volatile materials, including by-product isopropyl chloride, were removed by rotary evaporation, leaving 200 g of residue. Analysis on a Varian gas chromatograph having a packed column ("GC Analysis") indicated  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  and  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  in a ratio of about 1:2, respectively. Distillation at 29 mmHg resulted

35

in 107.9 g of starting material (boiling point from about 105 to 107 °C), and 36.9 g (46% yield) of  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  (boiling point from about 85 to 90 °C).

**Example 3. Fluorination of  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  with  $\text{HF/SbCl}_5$**

5        A 600-mL monel autoclave equipped with mechanical stirrer was charged with 8.7 g  $\text{SbCl}_5$  and cooled to -27 °C. The autoclave was then evacuated and charged with 49.8 g of anhydrous HF. The contents were cooled to -40 °C, and 44 g  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  was added. The reactor was then connected to a packed column/condenser assembly. The condenser was maintained at -20 °C. The reaction  
10        mixture was heated to 135 °C over 2.25 hours and maintained at that temperature for an additional 2 hours. During this heating period, the pressure in the autoclave was maintained from about 1965 to 2655 KPa (300 - 400 psig) by periodically venting pressure (HCl by-product) in excess of 2655 KPa (400 psig). Venting was done from the top of the condenser to a cold aqueous KOH scrubber which was connected to -78  
15        °C cold trap. The reactor was then completely vented to the cold trap. 18.5 g of a colorless liquid were collected. The identity of this liquid was determined by GC analysis to be 84%  $\text{CF}_3\text{CH}_2\text{CHF}_2$  (corresponding to a yield of 57%) and 11%  $\text{CF}_3\text{CH}_2\text{CHClF}$ .

20        **Example 4. Fluorination of  $\text{CF}_3\text{CH}_2\text{CHCl}_2$  with  $\text{HF/SbF}_5$**

      The experiment described in Example 3 was repeated except that  $\text{CF}_3\text{CH}_2\text{CHCl}_2$  was used as the starting material. To the apparatus described in Example 3 was charged 8.2 g  $\text{SbF}_5$ , 41 g HF, and 37 g  $\text{CF}_3\text{CH}_2\text{CHCl}_2$ . (The  $\text{CF}_3\text{CH}_2\text{CHCl}_2$  was obtained via the room temperature photochlorination of  
25        commercially available  $\text{CF}_3\text{CH}_2\text{CH}_2\text{Cl}$ .) This mixture was heated with stirring to about 130 - 135 °C for 4.5 hours at a maximum operating pressure of 3450 KPa. 18.1 g (corresponding to a yield of 57%) of a colorless liquid were recovered. GC analysis identified the material as 94% pure HFC-245fa.

30        **Example 5. Fluorination of  $\text{CF}_3\text{CH}_2\text{CHCl}_2$  with  $\text{HF/SbCl}_5$  at 150 - 160 °C and Low Operating Pressure**

      The experiment described in Example 3 was repeated except that  $\text{CF}_3\text{CH}_2\text{CHCl}_2$  was used as the starting material. To the apparatus described in Example 3 was charged 9.5 g  $\text{SbCl}_5$ , 47.9 g HF, and 34.6 g  $\text{CF}_3\text{CH}_2\text{CHCl}_2$ . This  
35        mixture was heated with stirring to about 150 - 160 °C for 3.5 hours and maintained at that temperature for an additional 2 hours. The maximum operating pressure, controlled by periodic venting of by-product HCl, was 1280 KPa. GC analysis of the crude reaction product indicated that it contained 71% HFC-245fa.

As illustrated by the above-described Examples, HFC-245fa is produced in high yield without the use of high temperatures or pressures and without using large quantities of expensive catalysts.

What is claimed is:

1. A process for the manufacture of 1,1,1,3,3-pentafluoropropane which comprises:

a) reacting a compound of the formula:



wherein  $w = 0$  or  $1$ , and  $y = 0 - 3$ , with hydrogen fluoride in the presence of a fluorination catalyst under conditions sufficient to produce a compound of the formula  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ .

10 2. The process of claim 1 wherein the fluorination catalyst is selected from the group consisting of pentavalent antimony halide, pentavalent niobium halide, pentavalent arsenic halide, pentavalent tantalum halide; pentavalent antimony mixed halide, pentavalent niobium mixed halide, pentavalent arsenic mixed halide, pentavalent tantalum mixed halide, and mixtures thereof.

15 3. The process of claim 2 wherein the fluorination catalyst has the formula  $\text{SbCl}_n\text{F}_{5-n}$ , where  $n$  is 0 to 5.

20 4. The process of claim 2 wherein said compound of the formula  $\text{CF}_y\text{Cl}_{3-y}\text{CH}_2\text{CHF}_w\text{Cl}_{2-w}$  is selected from the group consisting of  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ ,  $\text{CF}_3\text{CH}_2\text{CHCl}_2$ ,  $\text{CFCl}_2\text{CH}_2\text{CHCl}_2$ ,  $\text{CF}_2\text{ClCH}_2\text{CHCl}_2$ ,  $\text{CFCl}_2\text{CH}_2\text{CHClF}$ ,  $\text{CF}_2\text{ClCH}_2\text{CHFCl}$ , and  $\text{CF}_3\text{CH}_2\text{CHFCl}$ .

25 5. The process of claim 2 wherein said compound of the formula  $\text{CF}_y\text{Cl}_{3-y}\text{CH}_2\text{CHF}_w\text{Cl}_{2-w}$  is  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ .

6. The process of claim 1 wherein said reaction is conducted at a temperature of from about  $50$  to about  $175^\circ\text{C}$ .

30 7. The process of claim 1 wherein the amount of  $\text{HF}$  used is about 1 to about 15 times the stoichiometric amount of  $\text{HF}$  to said compound of the formula  $\text{CF}_y\text{Cl}_{3-y}\text{CH}_2\text{CHF}_w\text{Cl}_{2-w}$ .

35 8. The process of claim 7 wherein said fluorination catalyst is present in an amount of from about 5 to about 50% by weight relative to the amount of compound of the formula  $\text{CF}_y\text{Cl}_{3-y}\text{CH}_2\text{CHF}_w\text{Cl}_{2-w}$  present.

9. A process for the manufacture of 1,1,1,3,3-pentafluoropropane which comprises:

a.) reacting  $\text{CCl}_4$  and vinyl chloride under conditions sufficient to produce a compound of the formula  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$ ; and

5                   b) reacting a compound of the formula  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  with hydrogen fluoride in the presence of a fluorination catalyst to produce a compound of the formula  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ .

10                   10. The process of claim 9 wherein said  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  is recovered prior to step b.

# INTERNATIONAL SEARCH REPORT

Int. onal Application No

PCT/US 95/08404

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C07C17/20 C07C19/08 C07C17/278 C07C19/01

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 522 639 (SOLVAY (SOCIÉTÉ ANONYME)) 13 January 1993 see the whole document ---	1-10
P,A	WO,A,95 04021 (ALLIEDSIGNAL INC.) 9 February 1995 see the whole document -----	1-10



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

21 September 1995

Date of mailing of the international search report

- 3. 10. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. ( + 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax ( + 31-70) 340-3016

Authorized officer

Bonnevalle, E

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 95/08404

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-522639	13-01-93	BE-A- 1005096 DE-D- 69202207 JP-A- 5201892	20-04-93 01-06-95 10-08-93
WO-A-9504021	09-02-95	US-A- 5395997	07-03-95